

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 Revision Date: 08-22-2017

Replaces:

1. Identification

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Automatic Transmission Fluid

Restrictions on use: Uses other than those described above

Name, address, and telephone number

ALLIED OIL & SUPPLY, INC.

of the chemical manufacturer,

2209 S. 24th Street

importer, or other responsible party:

Omaha, NE 68108

Phone number: 402-344-4343 800-333-3717

E-mail address: info@allied-oil.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

Hazards not otherwise classified: No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	No data available	72623-87-1	90 - 99
Mineral oil	No data available	8012-95-1	3 - 7

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Eye Contact: None expected to be needed, however, use an eye wash to remove a

chemical from your eye regardless of the level of hazard.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder.

Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

None Known

Indication of immediate medical attention and special treatment

needed, if necessary:

No additional first aid information available.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Special protective equipment and

precautions for fire-fighters:

No data available

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 Revision Date: 08-22-2017

Replaces:

the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing the

material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk

product transfer. No data available

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions: Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Lubricating oils	5 mg/m3	5 mg/m3	10 mg/m3	No data available
(petroleum), C20-50,				
hydrotreated neutral oil-				
based				
Mineral oil	5 mg/m3 TWA	5 mg/m3 TWA	No STEL	2500 mg/m3 IDLH
		(excluding metal		
		working fluids,		
		highly & severely		
		refined, inhalable		
		fraction)		

Appropriate engineering controls:

Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 Revision Date: 08-22-2017

Replaces:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or using this material should be equipped with an

eyewash and safety shower.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room

ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible. None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Respirator Type(s): None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye protection: No special requirements under normal industrial use. Wear goggles and

a Face shield.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety

goggles plus a face shield.

Gloves: Nitrile

Other protective equipment: Wear goggles and a Face shield. Where contact is likely, wear chemical

resistant gloves, a chemical suit, rubber boots, and chemical safety

goggles plus a face shield.

General hygiene conditions: No data available

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid Color: Red

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 Revision Date: 08-22-2017

Replaces:

Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data available

Initial boiling point and boiling range

(°C):

Flash Point (°C): 201

Evaporation Rate:No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Lower flammability or explosive

limits:

Not established

Not established

270

No data available

Vapor pressure:

No data available

Vapor density:

No data available

Relative density:

0.85

Solubility(ies): Insoluble

Partition coefficient: n-octanol/water: 3.9

Auto-ignition temperature:No data availableDecomposition Temperature:Not determined

Viscosity: 28.56
Volatile organic compound (VOC) 0.000000

content and percentage of volatiles:

10. Stability and reactivity

Reactivity:

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: No data available

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

No data available

Symptoms related to the physical,

chemical and toxicological

characteristics:

None Known

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Although this product has a low order of acute oral toxicity, aspiration of

minute amounts into the lungs during ingestion or vomiting may cause

mild to severe pulmonary injury and possibly death.

Skin Contact: This material is estimated to be moderately irritating (Primary Irritation

Index is 3.0 - 5.0 [rabbits]). Can cause moderate skin irritation, defatting,

and dermatitis. Not likely to cause permanent damage.

Absorption: Likely to be practically non-toxic based on animal data.

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs"). Likely to be

practically non-toxic based on animal data.

Eye Contact: This material is likely to be non-irritating to eyes based on animal data.

Sensitization: No data available

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: No data available

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Mineral oil			Inhalation LC50 (4h) Rat 2062 ppm
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	OLD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat 2.18 mg/L

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial,

No data available

where available):

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Lubricating oils (petroleum), C20-50, hydrotreated neutral oilbased	72623-87-1	> 1000 mg/L	No data available	Aquatic LC50 (96h) > 5000 mg/L

Persistence and degradability: No data available

Bioconcentration is not expected to occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

No data available

13. Disposal considerations

Description of waste residues and

Spent or discarded material is non-hazardous according to environmental

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

information on their safe handling and methods of disposal, including the disposal of any contaminated regulations.

packaging:

Contaminated packaging: Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:Not classified as hazardous for transport (DOT, TDG, IMO/IMDG,

IATA/ICAO).

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs

to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

Regulated Components:

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Mineral oil	8012-95-1	N	N	N	N
Methacrylate copolymer	Confidentia I	N	N	N	N

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Mineral oil	8012-95-1	N	N	N	N
Methacrylate copolymer	Confidentia I	N	N	N	N

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N	N
Mineral oil	8012-95-1	Υ	Υ	Υ	N	Υ
Methacrylate copolymer	Confidentia I	N	N	N	N	N

16. Other information, including date of preparation or last revision.

Product identifier used on the label: General Motors ATF - DEX VI

Stock Number: ALATF020 **Revision Date:** 08-22-2017

Replaces:

SDS Prepared by: TPRUETT

Revision Date: 08-22-2017

Revision Number:

Reason for revision: NEW

References: No data available
Other Info: No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.