

Printed On: October 25, 2016

## Description

ALLIED MEGA EHF BULKFLUID

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	32.35
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8636
Viscosity @ 40°C cSt	ASTM D445	46.12
Viscosity @ 100°C cSt	ASTM D445	9.785
Viscosity Index	ASTM D2270	205
Pour Point °C (°F)	ASTM D5950	-33°C (-27°F)
Oxidation Hours	ASTM D943	5,000
Color	ASTM D1500	0.5
Zinc, wt. %	ASTM D5185	0.041
Phosphorus, wt. %	ASTM D5185	0.033
Calcium, wt. %	ASTM D5185	0.003
Sulfur, wt. %	ASTM D4951	0.065

## Claims Information

Cincinnati/MAG IAS P-70	Suitable for Use
Parker Denison HF-0, HF-1	Suitable for Use
Parker Denison HF-2	Suitable for Use
Sperry Vickers/Eaton I-286-S, M-2950-S	Suitable for Use
US Steel 127, 136	Suitable for Use
DIN 51524, Part 1,2,3	Suitable for Use
General Motors LS-2	Suitable for Use
JCMAS HK	Suitable for Use
Bosch Rexroth	Suitable for Use